

INDUST VM 333D CB H

TM-VM.D0CB0333H

Click on the selected icon to download the file:



No: 3025



No: 5047/2023
Valid until:
26.07.2028



No: 3025




No: 3025



No: V1.0



Producer	TM TECHNOLOGIE
Category	emergency luminaires
Application	evacuation route direction
Family	INDUST VM
Colour structure	raw
Version	CB - central battery
Operating mode	CB
Protection degree	IP66, IP69
Impact protection degree	IK08
Appliance classes	I
Material	stainless steel
Installation method*	surface, wall
Adapted to use a pictogram	yes
Pictogram dimensions	353, 2x359, 2 mm
Evacuation sign dimensions	300x300 mm
Pictogram type	plexiglass PMMA
Luminous flux	>200 cd/m²
Visibility	60 m
Colour temperature	5700 K
Nominal voltage AC	220-240 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	1.5 W
LED lifetime	50000 h
Minimum temperature	-25 °C
Maximum temperature	+45 °C
Battery	-
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	714 mm x 223 mm x 1103 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.