



## CERTIFICATE OF COMPLIANCE

| This certificate of compliance validates the following                    |                                                                                                                                                                                                                        |                           |                                                                                                                                                                                                                                 |
|---------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>TEST REPORTS<br/>NUMBER</b> 'Assessment<br>Reports' are not acceptable | 1) 3432067.50<br>2) 3432068.50<br>3) 3432069.50<br>4) 3432070.50<br>5) 3432073.50<br>6) 3432075.50<br>7) 3432076.50<br>8) 3432077.50<br>9) 3432079.50<br>10) 3432895.51<br>11) 3431394.52                              | <b>CERTIFICATE NUMBER</b> | 2314475.01-UAE<br>Refers to ENEC certificates<br>1) 88-142217<br>2) 88-141435<br>3) 88-141635<br>4) 88-141776<br>5) 88-141849<br>6) 88-141917<br>7) 88-141985<br>8) 88-142033<br>9) 88-142062<br>10) 88-147575<br>11) 88-146912 |
| <b>DATE OF ISSUE</b>                                                      | 1) 03 July 2024<br>2) 28 May 2024<br>3) 03 July 2024<br>4) 03 July 2024<br>5) 04 July 2024<br>6) 04 July 2024<br>7) 04 July 2024<br>8) 04 July 2024<br>9) 04 July 2024<br>10) 01 October 2024<br>11) 24 September 2024 | <b>DATE OF ISSUE</b>      | 19 October 2026                                                                                                                                                                                                                 |
| <b>DATE OF EXPIRY</b>                                                     | By expiration of the<br>standard(s)                                                                                                                                                                                    | <b>DATE OF EXPIRY</b>     | 19 October 2028                                                                                                                                                                                                                 |

| Manufacturer details                                                           |                                                                                 |                                |                                                                                                                                                                            |
|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>NAME OF<br/>FACTORY/<br/>MANUFACTURER</b>                                   | TM Technologie Sp.z.o.o                                                         | <b>NAME OF THE<br/>BRAND</b>   | TM TECHNOLOGIE                                                                                                                                                             |
| <b>FACTORY<br/>ADDRESS /<br/>REGION</b><br>(STREET / TOWN / CITY /<br>COUNTRY) | Morawica 355<br>32-084 Morawica<br>Poland                                       | <b>MODEL / NO</b>              | ONTEC S series<br>TM.ONTEC C/D, E, G, R series<br>TM.PRIMO C/D, E, G, R series<br>TM.ONTEC S20 series<br>ONTEC S30 series<br><br>See appendix 1 for full models<br>details |
| <b>WEBSITE</b>                                                                 | <a href="https://www.tmtechnologie.pl/en/">https://www.tmtechnologie.pl/en/</a> | <b>LOGO ON THE<br/>PRODUCT</b> |  TM TECHNOLOGIE                                                                       |
| <b>TEL</b>                                                                     | +48 12 444 60 60                                                                | <b>EMAIL</b>                   | <a href="mailto:biuro@tmtechnologie.pl">biuro@tmtechnologie.pl</a>                                                                                                         |



| Product Details From Test Report                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Reference<br>Test<br>Report<br>page NO |
|----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| <b>DESCRIPTION OF THE PRODUCT</b><br>(TECHNICAL DETAILS FROM TEST REPORT, SUCH AS ACTUAL FIRE RATINGS/DIMENSIONS/THICKNESS/ SENSITIVITY ETC) | Emergency lighting luminaires (centrally supplied) with LED light source – 210-250 Vac; 186-254 Vdc; 0/50-60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 2                                      |
| <b>TEST STANDARD</b><br>(SUCH AS ASTM/BS EN/ DN ETC)                                                                                         | IEC 60598-1: 2020 (representative for EN IEC 60598-1:2021 + A11:2022).<br>IEC 60598-2-22: 2021 (representative for EN IEC 60598-2-22:2022)<br><br>Title: Particular requirements – Luminaires for emergency lighting<br>Specifies requirements for emergency lighting luminaires, such as electrical safety, electrical insulation, proper earthing, emergency lighting performance, duration, ingress protection ratings, mechanical strength, correct labeling, operating manual, flammability of material used (Glow-wire test).                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1, 4                                   |
| <b>TEST DESCRIPTION</b>                                                                                                                      | Product test were done at the facilities of:<br><br><br><br>The following tests were part of the certification process:<br><ul style="list-style-type: none"> <li>- Classification</li> <li>- Product Marking</li> <li>- Construction</li> <li>- Creepage distances and clearances</li> <li>- Provision for earthing</li> <li>- Screw terminals</li> <li>- Screwless terminals and electrical connections</li> <li>- External and internal wiring</li> <li>- Protection against electric shock</li> <li>- Endurance test and thermal test</li> <li>- Resistance to dust and moisture</li> <li>- Isolation Resistance and electrical strength</li> <li>- Resistance to heat and fire tracking</li> <li>- Photometric data</li> <li>- Changeover operation</li> <li>- High Temperature operation</li> <li>- Battery charger for self-contained emergency luminaires</li> <li>- Test devices for emergency operation</li> <li>- Annexes (A through E, 1 through 4)</li> <li>- Attachment (1 through 4)</li> </ul> | -                                      |



|                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <b>SPECIFICATION OF TEST SPECIMEN</b>                                                                                                                                                                                                                                                                                                              | <p>The complete above mentioned tests have been carried out on models considered as representative of the listed models. (see appendix 1)</p> <p>The differences among the models in the series consist of minor differences in dimensions, lumen output and mounting options.</p>                                                                                                                                                                                                                                                               |  |
| <b>TEST RESULT</b><br>(SUCH AS PASSED CRITERIA___/<br>COMPLIED TO___/<br>DURATION___OBSERVATION___/ETC)                                                                                                                                                                                                                                            | <p>All applicable clauses as mentioned in the Test Report have passed the test.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |  |
| <b>PRODUCT APPLICATION GUIDELINE (END USE)</b><br>(CLEARLY STATE THE END USE WITH SPECIFIC APPLICATION, SUCH AS EXACT FIRE RATING/TO BE INSTALLED IN___/TO BE INSTALLED AT___/TO BE CONNECTED WITH___/TO BE INSTALLED WITH___ ETC ALONG WITH ANY WARNINGS SUCH AS NOT TO BE USED IN___/NOT TO BE INSTALLED AT___/ NOT TO BE INSTALLED WITH___ ETC. | <p>Emergency luminaires enables safe escape from a location in the event of failure of the normal mains supply.</p> <p>Centrally supplied luminaires are connected to a central battery system for a minimum of 3 hours duration in case of mains failure.</p> <p>Emergency are provided for emergency escape lighting for public and industrial premises and buildings.</p> <p>These luminaires are for fixed mounting and installation, which can be recessed mounting.</p> <p>Compatibility with central battery system: TM-CB A; TM-CB M</p> |  |



| Laboratory and Certification body details                                                                              |                                                                               |                                                                                                                |                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| NAME OF CERTIFICATION BODY                                                                                             | DEKRA Certification B.V.<br>                                                  | NAME OF TEST FACILITY                                                                                          | DEKRA Testing and Certification GmbH                                                               |
| CERTIFICATION BODY ADDRESS / REGION<br>(STREET / TOWN / CITY / COUNTRY)                                                | Meander 1051<br>6825 MJ Arnhem<br>The Netherlands                             | TEST FACILITY ADDRESS / REGION<br>(STREET / TOWN / CITY / COUNTRY)                                             | Enderstrasse 92b<br>01277 Dresden<br>Germany                                                       |
| WEBSITE                                                                                                                | <a href="http://www.dekra-certification.com">www.dekra-certification.com</a>  | WEBSITE                                                                                                        | <a href="http://www.dekra-testing-and-certification.de">www.dekra-testing-and-certification.de</a> |
| TEL                                                                                                                    | +31 88 96 83000                                                               | TEL                                                                                                            | +49 351 2118 1410                                                                                  |
| EMAIL                                                                                                                  | <a href="mailto:lighting@dekra.com">lighting@dekra.com</a>                    | EMAIL                                                                                                          | <a href="mailto:dte-lighting@dekra.com">dte-lighting@dekra.com</a>                                 |
| ACCREDITED BY<br>(NAME OF ACCREDITATION BODY WHICH ISSUED ACCREDITATION TO THE CERTIFICATION BODY, ALONG WITH WEBSITE) | Dutch Accreditation Council RVA<br><a href="http://www.rva.nl">www.rva.nl</a> | ACCREDITED BY<br>(NAME OF ACCREDITATION BODY WHICH ISSUED ACCREDITATION TO THE LABORATORY, ALONG WITH WEBSITE) | DAkks                                                                                              |
| AS PER<br>(STANDARD TO WHICH THE CERTIFICATION BODY IS ACCREDITED TO)                                                  | ISO/IEC 17065                                                                 | AS PER<br>(STANDARD TO WHICH YOUR ORGANIZATION IS ACCREDITED TO)                                               | ISO/IEC 17025:2018                                                                                 |
| VALIDITY<br>(EXPIRY DATE OF CERTIFICATION BODY ACCREDITATION)                                                          | 1 May 2030                                                                    | VALIDITY<br>(EXPIRY DATE OF LABORATORY ACCREDITATION)                                                          | 29 October 2030                                                                                    |
| REFERENCE NUMBER:<br>(CERTIFICATION BODY ACCREDITATION REFERENCE NUMBER TO VERIFY ON THE ACCREDITOR'S WEBSITE)         | C001                                                                          | REFERENCE NUMBER:<br>(THE LABORATORY ACCREDITATION REFERENCE NUMBER TO VERIFY ON THE ACCREDITOR'S WEBSITE)     | D-PL-17438-01-04                                                                                   |
| CERTIFICATION MARK                                                                                                     |                                                                               |                                                                                                                |                                                                                                    |



| (ENDORSEMENT) TO BE SIGNED BY MANUFACTURER                                         |                                                                                                 |                       |                                                  |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------|--------------------------------------------------|
| NAME OF MANUFACTURER'S SIGNATORY                                                   | Krzysztof Dziedzic                                                                              | SIGNATURE             | <i>Krzysztof Dziedzic</i><br>Dyrektor Techniczny |
| EMAIL / TEL                                                                        | <a href="mailto:k.dziedzic@tmtechnologie.pl">k.dziedzic@tmtechnologie.pl</a><br>+48 602 514 747 | FACTORY OFFICIAL SEAL |                                                  |
| NOTES: I Undertake that all data and information provided are genuine and accurate |                                                                                                 |                       |                                                  |

| (ENDORSEMENT) TO BE SIGNED BY CERTIFICATION BODY                                   |                                                                               |                                  |  |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|----------------------------------|--|
| NAME OF CERTIFICATION BODY SIGNATORY                                               | B.T.M. Holtus                                                                 | SIGNATURE                        |  |
| EMAIL / TEL                                                                        | <a href="mailto:lighting@dekra.com">lighting@dekra.com</a><br>+31 88 96 83000 | CERTIFICATION BODY OFFICIAL SEAL |  |
| NOTES: I Undertake that all data and information provided are genuine and accurate |                                                                               |                                  |  |

#### APPENDIX 1 – FULL LIST OF MODELS



## APPENDIX 1: List of models

### 1) For ONTEC S types:

| Model              | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|--------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| ONTEC S M2 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 260          |
| ONTEC S M2 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 260          |
| ONTEC S M2 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 260          |
| ONTEC S M2 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 260          |
| ONTEC S E1P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | N/A          |
| ONTEC S E1P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | N/A          |
| ONTEC S E1P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | N/A          |
| ONTEC S E1P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | N/A          |
| ONTEC S C1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 225          |
| ONTEC S W1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 204          |
| ONTEC S F1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 226          |
| ONTEC S C1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 225          |
| ONTEC S W1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 204          |
| ONTEC S F1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 226          |
| ONTEC S C1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 225          |
| ONTEC S W1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 204          |
| ONTEC S F1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 226          |
| ONTEC S C1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 225          |
| ONTEC S W1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 204          |
| ONTEC S F1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 226          |



| Model             | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| ONTEC S M5 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 576          |
| ONTEC S C2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 453          |
| ONTEC S W2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 388          |
| ONTEC S F2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 439          |
| ONTEC S M5 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 576          |
| ONTEC S C2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 453          |
| ONTEC S W2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 388          |
| ONTEC S F2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 439          |
| ONTEC S M5 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 576          |
| ONTEC S C2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 453          |
| ONTEC S W2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 388          |
| ONTEC S F2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 439          |
| ONTEC S M5 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 576          |
| ONTEC S C2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 453          |
| ONTEC S W2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 388          |
| ONTEC S F2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 439          |
| ONTEC S M1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 360          |
| ONTEC S M1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 360          |
| ONTEC S M1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 360          |
| ONTEC S M1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 360          |
| ONTEC S C1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 282          |
| ONTEC S W1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 289          |
| ONTEC S F1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP65      | 290          |



| Model          | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| ONTEC S C1 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 282          |
| ONTEC S W1 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 289          |
| ONTEC S F1 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP65      | 290          |
| ONTEC S C1 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 282          |
| ONTEC S W1 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 289          |
| ONTEC S F1 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 290          |
| ONTEC S C1 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 282          |
| ONTEC S W1 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 289          |
| ONTEC S F1 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP65      | 290          |

## 2) For ONTEC C/D types:

| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC C M1 01 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 140          |
| TM.ONTEC C M1 01 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 140          |
| TM.ONTEC C M1 01 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 140          |
| TM.ONTEC C M1 01 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 140          |
| TM.ONTEC C C1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 128          |
| TM.ONTEC C C1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 128          |
| TM.ONTEC C C1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 128          |
| TM.ONTEC C C1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 128          |
| TM.ONTEC C W1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 126          |
| TM.ONTEC C W1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 126          |
| TM.ONTEC C W1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 126          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC C W1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 126          |
| TM.ONTEC C S1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 133          |
| TM.ONTEC C S1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 133          |
| TM.ONTEC C S1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 133          |
| TM.ONTEC C S1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 133          |
| TM.ONTEC C F1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 136          |
| TM.ONTEC C F1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 136          |
| TM.ONTEC C F1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 136          |
| TM.ONTEC C F1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 136          |
| TM.ONTEC C M1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 338          |
| TM.ONTEC C M1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 338          |
| TM.ONTEC C M1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 338          |
| TM.ONTEC C M1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 338          |
| TM.ONTEC C C1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 297          |
| TM.ONTEC C C1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 297          |
| TM.ONTEC C C1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 297          |
| TM.ONTEC C C1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 297          |
| TM.ONTEC C W1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 303          |
| TM.ONTEC C W1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 303          |
| TM.ONTEC C W1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 303          |
| TM.ONTEC C W1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 303          |
| TM.ONTEC C S1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 321          |
| TM.ONTEC C S1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 321          |



| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC C S1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 321          |
| TM.ONTEC C S1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 321          |
| TM.ONTEC C F1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 323          |
| TM.ONTEC C F1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 323          |
| TM.ONTEC C F1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 323          |
| TM.ONTEC C F1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 323          |
| TM.ONTEC C M2 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 288          |
| TM.ONTEC C M2 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC C M2 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC C M2 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC C C1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 260          |
| TM.ONTEC C C1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 260          |
| TM.ONTEC C C1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 260          |
| TM.ONTEC C C1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 260          |
| TM.ONTEC C W1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 258          |
| TM.ONTEC C W1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC C W1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC C W1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC C S1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 273          |
| TM.ONTEC C S1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC C S1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC C S1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC C F1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 279          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC C F1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC C F1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC C F1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC C M2H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 393          |
| TM.ONTEC C M2H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 393          |
| TM.ONTEC C M2H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 393          |
| TM.ONTEC C M2H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 393          |
| TM.ONTEC C C1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 353          |
| TM.ONTEC C C1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 353          |
| TM.ONTEC C C1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 353          |
| TM.ONTEC C C1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 353          |
| TM.ONTEC C W1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 350          |
| TM.ONTEC C W1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 350          |
| TM.ONTEC C W1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 350          |
| TM.ONTEC C W1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 350          |
| TM.ONTEC C S1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 373          |
| TM.ONTEC C S1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 373          |
| TM.ONTEC C S1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 373          |
| TM.ONTEC C S1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 373          |
| TM.ONTEC C F1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 380          |
| TM.ONTEC C F1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 380          |
| TM.ONTEC C F1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 380          |
| TM.ONTEC C F1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 380          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC D M1 01 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 140          |
| TM.ONTEC D M1 01 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 140          |
| TM.ONTEC D M1 01 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 140          |
| TM.ONTEC D M1 01 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 140          |
| TM.ONTEC D C1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 128          |
| TM.ONTEC D C1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 128          |
| TM.ONTEC D C1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 128          |
| TM.ONTEC D C1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 128          |
| TM.ONTEC D W1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 126          |
| TM.ONTEC D W1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 126          |
| TM.ONTEC D W1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 126          |
| TM.ONTEC D W1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 126          |
| TM.ONTEC D S1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 133          |
| TM.ONTEC D S1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 133          |
| TM.ONTEC D S1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 133          |
| TM.ONTEC D S1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 133          |
| TM.ONTEC D F1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 136          |
| TM.ONTEC D F1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 136          |
| TM.ONTEC D F1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 136          |
| TM.ONTEC D F1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 136          |
| TM.ONTEC D M1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 338          |
| TM.ONTEC D M1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 338          |
| TM.ONTEC D M1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 338          |



| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC D M1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 338          |
| TM.ONTEC D C1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 279          |
| TM.ONTEC D C1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC D C1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC D C1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC D W1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 303          |
| TM.ONTEC D W1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 303          |
| TM.ONTEC D W1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 303          |
| TM.ONTEC D W1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 303          |
| TM.ONTEC D S1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 321          |
| TM.ONTEC D S1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 321          |
| TM.ONTEC D S1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 321          |
| TM.ONTEC D S1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 321          |
| TM.ONTEC D F1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 323          |
| TM.ONTEC D F1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 323          |
| TM.ONTEC D F1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 323          |
| TM.ONTEC D F1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 323          |
| TM.ONTEC D M2 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 288          |
| TM.ONTEC D M2 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC D M2 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC D M2 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC D C1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 260          |
| TM.ONTEC D C1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 260          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC D C1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 260          |
| TM.ONTEC D C1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 260          |
| TM.ONTEC D W1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 258          |
| TM.ONTEC D W1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC D W1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC D W1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC D S1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 273          |
| TM.ONTEC D S1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC D S1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC D S1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC D F1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 279          |
| TM.ONTEC D F1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC D F1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC D F1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.ONTEC D M2H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 393          |
| TM.ONTEC D M2H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 393          |
| TM.ONTEC D M2H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 393          |
| TM.ONTEC D M2H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 393          |
| TM.ONTEC D C1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 353          |
| TM.ONTEC D C1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 353          |
| TM.ONTEC D C1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 353          |
| TM.ONTEC D C1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 353          |
| TM.ONTEC D W1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 350          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC D W1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 350          |
| TM.ONTEC D W1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 350          |
| TM.ONTEC D W1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 350          |
| TM.ONTEC D S1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 373          |
| TM.ONTEC D S1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 373          |
| TM.ONTEC D S1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 373          |
| TM.ONTEC D S1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 373          |
| TM.ONTEC D F1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 380          |
| TM.ONTEC D F1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 380          |
| TM.ONTEC D F1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 380          |
| TM.ONTEC D F1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 380          |



### 3) For PRIMO C/D types:

| Model               | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|---------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO C M1 CB    | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 263          |
| TM.PRIMO C M1 CBA   | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 263          |
| TM.PRIMO C M1 CB+   | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 263          |
| TM.PRIMO C M1 CBM   | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 263          |
| TM.PRIMO C C1 CB    | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 279          |
| TM.PRIMO C C1 CBA   | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.PRIMO C C1 CB+   | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.PRIMO C C1 CBM   | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.PRIMO C W1 CB    | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 278          |
| TM.PRIMO C W1 CBA   | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 278          |
| TM.PRIMO C W1 CB+   | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 278          |
| TM.PRIMO C W1 CBM   | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 278          |
| TM.PRIMO C S1 CB    | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 314          |
| TM.PRIMO C S1 CBA   | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 314          |
| TM.PRIMO C S1 CB+   | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 314          |
| TM.PRIMO C S1 CBM   | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 314          |
| TM.PRIMO C F1 CB    | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 293          |
| TM.PRIMO C F1 CBA   | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 293          |
| TM.PRIMO C F1 CB+   | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 293          |
| TM.PRIMO C F1 CBM   | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 293          |
| TM.PRIMO C M1 01 CB | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 109          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO C M1 01 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 109          |
| TM.PRIMO C M1 01 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 109          |
| TM.PRIMO C M1 01 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 109          |
| TM.PRIMO C C1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 120          |
| TM.PRIMO C C1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 120          |
| TM.PRIMO C C1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 120          |
| TM.PRIMO C C1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 120          |
| TM.PRIMO C W1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 116          |
| TM.PRIMO C W1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 116          |
| TM.PRIMO C W1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 116          |
| TM.PRIMO C W1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 116          |
| TM.PRIMO C S1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 130          |
| TM.PRIMO C S1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 130          |
| TM.PRIMO C S1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 130          |
| TM.PRIMO C S1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 130          |
| TM.PRIMO C F1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 123          |
| TM.PRIMO C F1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 123          |
| TM.PRIMO C F1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 123          |
| TM.PRIMO C F1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 123          |
| TM.PRIMO C M2 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 224          |
| TM.PRIMO C M2 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 224          |
| TM.PRIMO C M2 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 224          |
| TM.PRIMO C M2 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 224          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO C C1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 244          |
| TM.PRIMO C C1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 244          |
| TM.PRIMO C C1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 244          |
| TM.PRIMO C C1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 244          |
| TM.PRIMO C W1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 237          |
| TM.PRIMO C W1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 237          |
| TM.PRIMO C W1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 237          |
| TM.PRIMO C W1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 237          |
| TM.PRIMO C S1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 267          |
| TM.PRIMO C S1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 267          |
| TM.PRIMO C S1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 267          |
| TM.PRIMO C S1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 267          |
| TM.PRIMO C F1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 253          |
| TM.PRIMO C F1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 253          |
| TM.PRIMO C F1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 253          |
| TM.PRIMO C F1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 253          |
| TM.PRIMO C M2H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 306          |
| TM.PRIMO C M2H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.PRIMO C M2H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.PRIMO C M2H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.PRIMO C C1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 331          |
| TM.PRIMO C C1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 331          |
| TM.PRIMO C C1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 331          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO C C1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 331          |
| TM.PRIMO C W1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 322          |
| TM.PRIMO C W1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 322          |
| TM.PRIMO C W1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 322          |
| TM.PRIMO C W1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 322          |
| TM.PRIMO C S1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 365          |
| TM.PRIMO C S1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 365          |
| TM.PRIMO C S1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 365          |
| TM.PRIMO C S1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 365          |
| TM.PRIMO C F1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 345          |
| TM.PRIMO C F1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 345          |
| TM.PRIMO C F1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 345          |
| TM.PRIMO C F1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 345          |
| TM.PRIMO D M1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 263          |
| TM.PRIMO D M1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 263          |
| TM.PRIMO D M1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 263          |
| TM.PRIMO D M1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 263          |
| TM.PRIMO D C1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 279          |
| TM.PRIMO D C1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.PRIMO D C1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.PRIMO D C1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 279          |
| TM.PRIMO D W1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 278          |
| TM.PRIMO D W1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 278          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO D W1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 278          |
| TM.PRIMO D W1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 278          |
| TM.PRIMO D S1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 314          |
| TM.PRIMO D S1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 314          |
| TM.PRIMO D S1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 314          |
| TM.PRIMO D S1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 314          |
| TM.PRIMO D F1 CB      | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 293          |
| TM.PRIMO D F1 CBA     | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 293          |
| TM.PRIMO D F1 CB+     | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 293          |
| TM.PRIMO D F1 CBM     | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 293          |
| TM.PRIMO D M1 01 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 109          |
| TM.PRIMO D M1 01 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 109          |
| TM.PRIMO D M1 01 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 109          |
| TM.PRIMO D M1 01 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 109          |
| TM.PRIMO D C1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 120          |
| TM.PRIMO D C1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 120          |
| TM.PRIMO D C1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 120          |
| TM.PRIMO D C1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 120          |
| TM.PRIMO D W1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 116          |
| TM.PRIMO D W1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 116          |
| TM.PRIMO D W1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 116          |
| TM.PRIMO D W1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 116          |
| TM.PRIMO D S1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 130          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO D S1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 130          |
| TM.PRIMO D S1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 130          |
| TM.PRIMO D S1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 130          |
| TM.PRIMO D F1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 123          |
| TM.PRIMO D F1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 123          |
| TM.PRIMO D F1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 123          |
| TM.PRIMO D F1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 123          |
| TM.PRIMO D M2 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 224          |
| TM.PRIMO D M2 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 224          |
| TM.PRIMO D M2 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 224          |
| TM.PRIMO D M2 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 224          |
| TM.PRIMO D C1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 244          |
| TM.PRIMO D C1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 244          |
| TM.PRIMO D C1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 244          |
| TM.PRIMO D C1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 244          |
| TM.PRIMO D W1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 237          |
| TM.PRIMO D W1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 237          |
| TM.PRIMO D W1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 237          |
| TM.PRIMO D W1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 237          |
| TM.PRIMO D S1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 267          |
| TM.PRIMO D S1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 267          |
| TM.PRIMO D S1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 267          |
| TM.PRIMO D S1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 267          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO D F1 02 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 253          |
| TM.PRIMO D F1 02 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 253          |
| TM.PRIMO D F1 02 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 253          |
| TM.PRIMO D F1 02 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 253          |
| TM.PRIMO D M2H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 306          |
| TM.PRIMO D M2H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.PRIMO D M2H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.PRIMO D M2H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.PRIMO D C1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 331          |
| TM.PRIMO D C1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 331          |
| TM.PRIMO D C1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 331          |
| TM.PRIMO D C1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 331          |
| TM.PRIMO D W1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 322          |
| TM.PRIMO D W1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 322          |
| TM.PRIMO D W1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 322          |
| TM.PRIMO D W1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 322          |
| TM.PRIMO D S1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 365          |
| TM.PRIMO D S1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 365          |
| TM.PRIMO D S1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 365          |
| TM.PRIMO D S1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 365          |
| TM.PRIMO D F1H 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 345          |
| TM.PRIMO D F1H 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 345          |
| TM.PRIMO D F1H 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 345          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO D F1H 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 345          |

4) For ONTEC E types:

| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC E E1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.ONTEC E E1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC E E1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC E E1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC E E1P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.ONTEC E E1P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC E E1P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC E E1P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |



5) For PRIMO E types:

| Model                 | Description /Application                                                 | Suppl voltage              | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO E 25E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 25E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 25E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 25E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 30E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 30E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 30E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 30E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 40E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 40E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 40E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 40E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 60E 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 60E 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 60E 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 60E 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 80E 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 80E 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 80E 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 80E 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 25P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |



| Model                 | Description /Application                                                 | Suppl voltage              | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO E 25P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 25P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 25P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 30P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 30P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 30P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 30P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 40P 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO E 40P 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 40P 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO E 40P 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |

6) For ONTEC G types:

| Model                 | Description /Application                                                 | Suppl voltage              | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC G E1E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.ONTEC G E1E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC G E1E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC G E1E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC G E1P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.ONTEC G E1P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC G E1P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC G E1P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |



7) For PRIMO G types:

| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO G 25E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 25E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 30E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40E 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 40E 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40E 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40E 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 25P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 30P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40P 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 40P 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO G 40P 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40P 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25D 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 25D 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25D 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 25D 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30D 03 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 30D 03 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30D 03 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 30D 03 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40D 04 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO G 40D 04 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40D 04 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO G 40D 04 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |



8) For ONTEC R types:

| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC R M1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 360          |
| TM.ONTEC R M1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 360          |
| TM.ONTEC R M1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 360          |
| TM.ONTEC R M1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 360          |
| TM.ONTEC R C1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 306          |
| TM.ONTEC R C1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.ONTEC R C1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.ONTEC R C1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 306          |
| TM.ONTEC R W1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 325          |
| TM.ONTEC R W1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 325          |
| TM.ONTEC R W1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 325          |
| TM.ONTEC R W1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 325          |
| TM.ONTEC R S1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 341          |
| TM.ONTEC R S1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 341          |
| TM.ONTEC R S1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 341          |
| TM.ONTEC R S1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 341          |
| TM.ONTEC R F1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 339          |
| TM.ONTEC R F1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 339          |
| TM.ONTEC R F1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 339          |
| TM.ONTEC R F1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 339          |
| TM.ONTEC R M2 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 288          |
| TM.ONTEC R M2 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 288          |



| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC R M2 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC R M2 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.ONTEC R C1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 246          |
| TM.ONTEC R C1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 246          |
| TM.ONTEC R C1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 246          |
| TM.ONTEC R C1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 246          |
| TM.ONTEC R W1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 258          |
| TM.ONTEC R W1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC R W1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC R W1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 258          |
| TM.ONTEC R S1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 273          |
| TM.ONTEC R S1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC R S1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC R S1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.ONTEC R F1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 271          |
| TM.ONTEC R F1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 271          |
| TM.ONTEC R F1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 271          |
| TM.ONTEC R F1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 271          |
| TM.ONTEC R M5 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 555          |
| TM.ONTEC R M5 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 555          |
| TM.ONTEC R M5 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 555          |
| TM.ONTEC R M5 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 555          |
| TM.ONTEC R C2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 465          |



| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.ONTEC R C2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 465          |
| TM.ONTEC R C2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 465          |
| TM.ONTEC R C2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 465          |
| TM.ONTEC R W2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 493          |
| TM.ONTEC R W2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 493          |
| TM.ONTEC R W2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 493          |
| TM.ONTEC R W2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 493          |
| TM.ONTEC R S2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 527          |
| TM.ONTEC R S2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 527          |
| TM.ONTEC R S2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 527          |
| TM.ONTEC R S2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 527          |
| TM.ONTEC R F2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 510          |
| TM.ONTEC R F2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 510          |
| TM.ONTEC R F2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 510          |
| TM.ONTEC R F2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 510          |
| TM.ONTEC R E1 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.ONTEC R E1 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC R E1 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.ONTEC R E1 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |



9) For PRIMO R types:

| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO R M1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 333          |
| TM.PRIMO R M1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 333          |
| TM.PRIMO R M1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 333          |
| TM.PRIMO R M1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 333          |
| TM.PRIMO R C1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 289          |
| TM.PRIMO R C1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 289          |
| TM.PRIMO R C1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 289          |
| TM.PRIMO R C1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 289          |
| TM.PRIMO R S1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 313          |
| TM.PRIMO R S1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 313          |
| TM.PRIMO R S1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 313          |
| TM.PRIMO R S1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 313          |
| TM.PRIMO R F1 CB     | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 311          |
| TM.PRIMO R F1 CBA    | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 311          |
| TM.PRIMO R F1 CB+    | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 311          |
| TM.PRIMO R F1 CBM    | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 311          |
| TM.PRIMO R M2 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 288          |
| TM.PRIMO R M2 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.PRIMO R M2 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.PRIMO R M2 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 288          |
| TM.PRIMO R C1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 246          |



| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO R C1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 246          |
| TM.PRIMO R C1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 246          |
| TM.PRIMO R C1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 246          |
| TM.PRIMO R S1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 273          |
| TM.PRIMO R S1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.PRIMO R S1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.PRIMO R S1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 273          |
| TM.PRIMO R F1 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 271          |
| TM.PRIMO R F1 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 271          |
| TM.PRIMO R F1 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 271          |
| TM.PRIMO R F1 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 271          |
| TM.PRIMO R C2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 465          |
| TM.PRIMO R C2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 465          |
| TM.PRIMO R C2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 465          |
| TM.PRIMO R C2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 465          |
| TM.PRIMO R S2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 527          |
| TM.PRIMO R S2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 527          |
| TM.PRIMO R S2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 527          |
| TM.PRIMO R S2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 527          |
| TM.PRIMO R F2 05 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | 510          |
| TM.PRIMO R F2 05 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | 510          |
| TM.PRIMO R F2 05 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 510          |
| TM.PRIMO R F2 05 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | 510          |



| Model                 | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating | Lumen output |
|-----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-----------|--------------|
| TM.PRIMO R 25P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO R 25P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 25P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 25P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 30P 01 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO R 30P 01 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 30P 01 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 30P 01 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 40P 02 CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP20      | N/A          |
| TM.PRIMO R 40P 02 CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 40P 02 CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |
| TM.PRIMO R 40P 02 CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | I            | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP20      | N/A          |

#### 10) For ONTEC S20 types:

| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating   | Lumen output            |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-------------|-------------------------|
| TM.ONTEC S20 M1 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP44 / IP65 | 154                     |
| TM.ONTEC S20 M2 CB   | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP44 / IP65 | 309                     |
| TM.ONTEC S20 M2X CB  | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | maintained                   | IP44 / IP65 | 154 (low)<br>309 (high) |
| TM.ONTEC S20 M1 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP44 / IP65 | 154                     |
| TM.ONTEC S20 M2 CB+  | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP44 / IP65 | 309                     |
| TM.ONTEC S20 M2X CB+ | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP44 / IP65 | 154 (low)<br>309 (high) |
| TM.ONTEC S20 M1 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP44 / IP65 | 154                     |
| TM.ONTEC S20 M2 CBA  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP44 / IP65 | 309                     |



| Model                | Description /Application                                                 | Supply voltage             | Safety class | Frequency   | Ambient temperature | Type of operation            | IP-rating   | Lumen output            |
|----------------------|--------------------------------------------------------------------------|----------------------------|--------------|-------------|---------------------|------------------------------|-------------|-------------------------|
| TM.ONTEC S20 M2X CBA | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -10 °C to +40 °C    | Maintained / non- maintained | IP44 / IP65 | 154 (low)<br>309 (high) |
| TM.ONTEC S20 M1 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP44 / IP65 | 154                     |
| TM.ONTEC S20 M2 CBM  | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP44 / IP65 | 309                     |
| TM.ONTEC S20 M2X CBM | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0; 50-60 Hz | -15 °C to +55 °C    | Maintained / non- maintained | IP44 / IP65 | 154 (low)<br>309 (high) |

#### 11) For ONTEC S30 types:

| Model                     | Description /Application                                                 | Supply voltage             | Safety class | Frequency  | Ambient temperature | Type of operation          | IP-rating     | Lumen output            |
|---------------------------|--------------------------------------------------------------------------|----------------------------|--------------|------------|---------------------|----------------------------|---------------|-------------------------|
| TM.ONTEC S30 M1X CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained                 | IP44/<br>IP65 | 184 (Low)<br>349 (High) |
| TM.ONTEC S30 M1X CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 184 (Low)<br>349 (High) |
| TM.ONTEC S30 M1X CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -10 °C to +40 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 184 (Low)<br>349 (High) |
| TM.ONTEC S30 M1X CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 184 (Low)<br>349 (High) |
| TM.ONTEC S30 M1X CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +20 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 184 (Low)<br>349 (High) |
| TM.ONTEC S30 M2 CB        | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained                 | IP44/<br>IP65 | 566                     |
| TM.ONTEC S30 M2 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 566                     |
| TM.ONTEC S30 M2 CBA       | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -10 °C to +40 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 566                     |
| TM.ONTEC S30 M2 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 566                     |
| TM.ONTEC S30 M2 CBA COLD  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +20 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 566                     |
| TM.ONTEC S30 C2 CB        | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained                 | IP44/<br>IP65 | 533                     |
| TM.ONTEC S30 C2 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 533                     |
| TM.ONTEC S30 C2 CBA       | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -10 °C to +40 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 533                     |
| TM.ONTEC S30 C2 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +55 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 533                     |
| TM.ONTEC S30 C2 CBA COLD  | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II           | 0;50-60 Hz | -25 °C to +20 °C    | Maintained /Non-maintained | IP44/<br>IP65 | 533                     |



|                          |                                                                          |                            |    |            |                  |                               |               |     |
|--------------------------|--------------------------------------------------------------------------|----------------------------|----|------------|------------------|-------------------------------|---------------|-----|
| TM.ONTEC S30 W2 CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 512 |
| TM.ONTEC S30 W2 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 512 |
| TM.ONTEC S30 W2 CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 512 |
| TM.ONTEC S30 W2 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 512 |
| TM.ONTEC S30 W2 CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 512 |
| TM.ONTEC S30 F2 CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 F2 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 F2 CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 F2 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 F2 CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 S2 CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 544 |
| TM.ONTEC S30 S2 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 544 |
| TM.ONTEC S30 S2 CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 544 |
| TM.ONTEC S30 S2 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 544 |
| TM.ONTEC S30 S2 CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 544 |
| TM.ONTEC S30 CC CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 537 |
| TM.ONTEC S30 CC CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 537 |
| TM.ONTEC S30 CC CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 537 |
| TM.ONTEC S30 CC CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 537 |
| TM.ONTEC S30 CC CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 537 |
| TM.ONTEC S30 FF CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 FF CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 554 |
| TM.ONTEC S30 FF CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 554 |



|                          |                                                                          |                            |    |            |                  |                            |               |      |
|--------------------------|--------------------------------------------------------------------------|----------------------------|----|------------|------------------|----------------------------|---------------|------|
| TM.ONTEC S30 FF CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 554  |
| TM.ONTEC S30 FF CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained /Non-maintained | IP44/<br>IP65 | 554  |
| TM.ONTEC S30 SC CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained                 | IP44/<br>IP65 | 536  |
| TM.ONTEC S30 SC CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 536  |
| TM.ONTEC S30 SC CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -10 °C to +40 °C | Maintained /Non-maintained | IP44/<br>IP65 | 536  |
| TM.ONTEC S30 SC CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 536  |
| TM.ONTEC S30 SC CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained /Non-maintained | IP44/<br>IP65 | 536  |
| TM.ONTEC S30 SW CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained                 | IP44/<br>IP65 | 529  |
| TM.ONTEC S30 SW CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 529  |
| TM.ONTEC S30 SW CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -10 °C to +40 °C | Maintained /Non-maintained | IP44/<br>IP65 | 529  |
| TM.ONTEC S30 SW CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 529  |
| TM.ONTEC S30 SW CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained /Non-maintained | IP44/<br>IP65 | 529  |
| TM.ONTEC S30 CW CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained                 | IP44/<br>IP65 | 522  |
| TM.ONTEC S30 CW CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 522  |
| TM.ONTEC S30 CW CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -10 °C to +40 °C | Maintained /Non-maintained | IP44/<br>IP65 | 522  |
| TM.ONTEC S30 CW CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained /Non-maintained | IP44/<br>IP65 | 522  |
| TM.ONTEC S30 CW CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained /Non-maintained | IP44/<br>IP65 | 522  |
| TM.ONTEC S30 M5 CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained                 | IP44/<br>IP65 | 1215 |
| TM.ONTEC S30 M5 CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -10 °C to +40 °C | Maintained /Non-maintained | IP44/<br>IP65 | 1215 |
| TM.ONTEC S30 M5 CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained /Non-maintained | IP44/<br>IP65 | 1215 |
| TM.ONTEC S30 C5 CB       | Emergency luminaire (non-addressable)                                    | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained                 | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 C5 CBA      | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -10 °C to +40 °C | Maintained /Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 C5 CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained /Non-maintained | IP44/<br>IP65 | 1145 |



|                           |                                               |                            |    |            |                  |                               |               |      |
|---------------------------|-----------------------------------------------|----------------------------|----|------------|------------------|-------------------------------|---------------|------|
| TM.ONTEC S30 W5 CB        | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1108 |
| TM.ONTEC S30 W5 CBA       | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1108 |
| TM.ONTEC S30 W5 CBA COLD  | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1108 |
| TM.ONTEC S30 F5 CB        | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1183 |
| TM.ONTEC S30 F5 CBA       | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1183 |
| TM.ONTEC S30 F5 CBA COLD  | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1183 |
| TM.ONTEC S30 S5 CB        | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 S5 CBA       | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 S5 CBA COLD  | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 CC5 CB       | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 CC5 CBA      | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 CC5 CBA COLD | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 FF5 CB       | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 FF5 CBA      | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 FF5 CBA COLD | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 SC5 CB       | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1162 |
| TM.ONTEC S30 SC5 CBA      | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1162 |
| TM.ONTEC S30 SC5 CBA COLD | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1162 |
| TM.ONTEC S30 SW5 CB       | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1139 |
| TM.ONTEC S30 SW5 CBA      | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1139 |
| TM.ONTEC S30 SW5 CBA COLD | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1139 |
| TM.ONTEC S30 CW5 CB       | Emergency luminaire (non-addressable)         | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -25 °C to +55 °C | Maintained                    | IP44/<br>IP65 | 1072 |
| TM.ONTEC S30 CW5 CBA      | Emergency luminaire (with addressable module) | 210-250V AC<br>186-254V DC | II | 0,50-60 Hz | -10 °C to +40 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1072 |



|                           |                                                                          |                            |    |            |                  |                               |               |      |
|---------------------------|--------------------------------------------------------------------------|----------------------------|----|------------|------------------|-------------------------------|---------------|------|
| TM.ONTEC S30 CW5 CBA COLD | Emergency luminaire (with addressable module)                            | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +20 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1072 |
| TM.ONTEC S30 M5 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1215 |
| TM.ONTEC S30 C5 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 W5 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1108 |
| TM.ONTEC S30 F5 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1183 |
| TM.ONTEC S30 S5 CBM       | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 CC5 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 FF5 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 SC5 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1162 |
| TM.ONTEC S30 SW5 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1139 |
| TM.ONTEC S30 CW5 CBM      | Emergency luminaire (with addressable module and modulated transmission) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1072 |
| TM.ONTEC S30 M5 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1215 |
| TM.ONTEC S30 C5 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 W5 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1108 |
| TM.ONTEC S30 F5 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1183 |
| TM.ONTEC S30 S5 CB+       | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 CC5 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1145 |
| TM.ONTEC S30 FF5 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1153 |
| TM.ONTEC S30 SC5 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1162 |
| TM.ONTEC S30 SW5 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1139 |
| TM.ONTEC S30 CW5 CB+      | Emergency luminaire (non-addressable, non-maintained operation possible) | 210-250V AC<br>186-254V DC | II | 0;50-60 Hz | -25 °C to +55 °C | Maintained<br>/Non-maintained | IP44/<br>IP65 | 1072 |

END